

C L A I M S

1. A sporting gear such as a roller skate which
2 moves with wheels, characterized in that one of a shoe
3 and a plate for mounting said shoe, and a frame for
4 supporting said wheels are provided, not less than two
5 parallel shafts which can move said shoe like a see-saw
6 are provided at front and rear portions of said shoe
7 separately, and one of said shoe and plate is connected
8 to said frame through said shafts, so that when said
9 shoe is moved like a see-saw about said shafts as
10 fulcrums, either a heel or toe can be separated from
11 said frame and raised, wherein brakes which act on said
12 front and rear wheels are connected to each other
13 through one of a belt, chain, and wire, and one of said
14 belt, chain, and wire is pulled at a raising portion of
15 one of said shoe and plate, or pushed at a lowering
16 portion thereof, or is pulled at said raising portion
17 and pushed at said lowering portion simultaneously, to
18 be able to brake said front and rear wheels
19 simultaneously.

2. A sporting gear according to claim 1,
2 characterized in that one of said shoe and said plate
3 for mounting said shoe is connected at a portion behind

4 a central portion thereof to said frame through one
5 shaft, so that when said shoe is moved like a see-saw
6 about said shaft as a fulcrum, a toe can be separated
7 from said frame and raised, wherein one of said belt,
8 chain, and wire is pulled at said raising portion of one
9 of said shoe and plate, or pushed at said lowering
10 portion thereof, or is pulled at said raising portion
11 and pushed at said lowering portion simultaneously, to
12 be able to brake said front and rear wheels
13 simultaneously.